

# RADAR MINS

18032

N1

## RADAR INSTRUMENT APPROACH MINIMUMS

### ATLANTIC CITY, NJ

Amdt 16, 04FEB16 (16035) (FAA)

ELEV 75

### ATLANTIC CITY INTL (ACY)

RADAR-1 124.6 327.125 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u>	<u>CEIL-VIS</u>
ASR	13		AB	<b>480/24</b>	405	(500-½)	CDE	<b>480/40</b>	405	(500-¾)
	4		AB	<b>480-1</b>	412	(500-1)	CDE	<b>480-1½</b>	412	(500-1½)
	31		AB	<b>480/55</b>	416	(500-1¼)	CDE	<b>480/60</b>	416	(500-1¼)
	22		AB	<b>560-1</b>	492	(500-1)	CDE	<b>560-1½</b>	492	(500-1½)
<b>Ⓢ</b> CIRCLING	ALL RWY		A	<b>560-1</b>	465	(500-1)	B	<b>600-1</b>	525	(600-1)
			C	<b>620-1½</b>	545	(600-1½)	D	<b>640-2</b>	565	(600-2)
			E	<b>760-2½</b>	685	(700-2½)				

For inoperative MALSRS, increase ASR S-13 CAT C/D/E visibility to RVR 6000.

Rwy 4 helicopter visibility reduction below ¾ SM not authorized.

### MC GUIRE FLD, (JOINT BASE MC GUIRE DIX LAKEHURST) (KWRI),

NJ (Amdt 1, 18032 USAF)

ELEV 141

RADAR (E) - 119.05 120.0 269.025 **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u>	<u>CEIL-VIS</u>
PAR	18'	3.0°/51/950	ABCDE	<b>322-¾</b>	200	(200-¾)
	36	3.0°/46/950	ABCDE	<b>429-1</b>	300	(300-1)

No-NOTAM MP: 0400-1100Z++ Mon-Fri, (by NOTAM if required).

PAR apch avbl 1200-0200Z++ Mon-Fri.

\*Rwy 18, VGSI and PAR glidepaths not coincident.

31 JAN 2019 to 28 FEB 2019

31 JAN 2019 to 28 FEB 2019

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS

18032


N1

NE-2

**RADAR INSTRUMENT APPROACH MINIMUMS**

**WHEELER-SACK AAF (KGTB), NY (Fort Drum) (1-Amdt 1, 2-Orig-A 14149 USA)**

ELEV **690**

RADAR<sup>1</sup>- 124.875 257.6 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
RADAR-1 PAR	3 <sup>2</sup> 3	3.0°/54/1038	ABCDE	<b>885</b> -½	200	(200-½)
	21 <sup>2</sup> 3	3.0°/58/1106	ABCDE	<b>877</b> -½	200	(200-½)
	33 <sup>4</sup>	3.0°/49/938	AB	<b>938</b> -¾	250	(300-¾)
			CDE	<b>938</b> -1	250	(300-1)
RADAR-2 ASR	21 <sup>5</sup>		AB	<b>1020</b> -½	343	(400-½)
			CDE	<b>1020</b> -¾	343	(400-¾)
	15 <sup>6</sup>		AB	<b>1100</b> -½	413	(500-½)
			CD	<b>1100</b> -¾	413	(500-¾)
			E	<b>1100</b> -1	413	(500-1)
	33 <sup>4</sup>		AB	<b>1140</b> -1	450	(500-1)
			C	<b>1140</b> -1¼	450	(500-1¼)
			DE	<b>1140</b> -1½	450	(500-1½)
	3 <sup>7</sup>		AB	<b>1240</b> -½	555	(600-½)
			C	<b>1240</b> -1	555	(600-1)
			D	<b>1240</b> -1¼	555	(600-1¼)
			E	<b>1240</b> -1½	555	(600-1½)
CIR <sup>8</sup>	ALL RWY		AB	<b>1240</b> -1	550	(600-1)
			C	<b>1240</b> -1½	550	(600-1½)
			D	<b>1240</b> -2	550	(600-2)
			E	<b>1520</b> -3	830	(900-3)

31 JAN 2019 to 28 FEB 2019

31 JAN 2019 to 28 FEB 2019

<sup>1</sup>Opr 1300-0500Z++ Mon-Fri exc federal hol. OT upon req.

<sup>2</sup>When ALS inop, increase CAT ABCDE vis to ¾ mile.

<sup>3</sup>VGSI and PAR glide path not coincident.

<sup>4</sup>Visibility reduction by helicopters NA.

<sup>5</sup>When ALS inop, increase CAT ABC vis to 1 mile, CAT DE vis to 1¼ miles.

<sup>6</sup>When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1¼ miles, CAT E vis to 1½ miles.

<sup>7</sup>When ALS inop, increase CAT AB vis to 1 mile, CAT C vis to 1½ miles, CAT D vis to 1¾ miles, CAT E vis to 2 miles.

<sup>8</sup>Circling not authorized E of Rwy 21 and 33. Circling not authorized for CAT E to Rwy 8-26 and Rwy 15-33. Circling not authorized for CAT B, C, and D to Rwy 8.

**RADAR INSTRUMENT APPROACH MINIMUMS**