

RADAR MINS

18032

N1

RADAR INSTRUMENT APPROACH MINIMUMS

ATLANTIC CITY, NJ

Amdt 16, 04FEB16 (16035) (FAA)

ELEV 75

ATLANTIC CITY INTL (ACY)

RADAR-1 124.6 327.125 **▽ ▲**

ASR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HATH/			MDA-VIS	HATH/	
	13		AB	480/24	405	(500-½)	CDE	480/40	405	(500-¾)
	4		AB	480-1	412	(500-1)	CDE	480-1½	412	(500-1½)
	31		AB	480/55	416	(500-1¼)	CDE	480/60	416	(500-1¼)
	22		AB	560-1	492	(500-1)	CDE	560-1½	492	(500-1½)
Ⓞ CIRCLING	ALL RWY		A	560-1	465	(500-1)	B	600-1	525	(600-1)
			C	620-1½	545	(600-1½)	D	640-2	565	(600-2)
			E	760-2½	685	(700-2½)				

For inoperative MALSR, increase ASR S-13 CAT C/D/E visibility to RVR 6000.

Rwy 4 helicopter visibility reduction below ¾ SM not authorized.

28 MAR 2019 to 25 APR 2019

MC GUIRE FLD, (JOINT BASE MC GUIRE DIX LAKEHURST) (KWRI),

NJ (Amdt 1, 18032 USAF)

ELEV 141

RADAR (E) - 119.05 120.0 269.025 **▽**

PAR	RWY	GS/TCH/RPI	CAT	DH/	HAT/	CEIL-VIS
				MDA-VIS	HATH/	
	18'	3.0°/51/950	ABCDE	322-¾	200	(200-¾)
	36	3.0°/46/950	ABCDE	429-1	300	(300-1)

No-NOTAM MP: 0400-1100Z++ Mon-Fri, (by NOTAM if required).

PAR apch avbl 1200-0200Z++ Mon-Fri.

*Rwy 18, VGSI and PAR glidepaths not coincident.

28 MAR 2019 to 25 APR 2019

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

18032


N1

NE-2

RADAR INSTRUMENT APPROACH MINIMUMS

WHEELER-SACK AAF (KGTB), NY (Fort Drum) (1-Amdt 1, 2-Orig-A 14149 USA)

ELEV **690**

RADAR¹- 124.875 257.6 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>	
RADAR-1 PAR	3 ^{2 3}	3.0°/54/1038	ABCDE	885-½	200	(200-½)	
	21 ^{2 3}	3.0°/58/1106	ABCDE	877-½	200	(200-½)	
	33 ⁴	3.0°/49/938	AB	938-¾	250	(300-¾)	
			CDE	938-1	250	(300-1)	
RADAR-2 ASR	21 ⁵		AB	1020-½	343	(400-½)	
			CDE	1020-¾	343	(400-¾)	
	15 ⁶		AB	1100-½	413	(500-½)	
			CD	1100-¾	413	(500-¾)	
			E	1100-1	413	(500-1)	
	33 ⁴		AB	1140-1	450	(500-1)	
			C	1140-1¼	450	(500-1¼)	
			DE	1140-1½	450	(500-1½)	
			AB	1240-½	555	(600-½)	
			C	1240-1	555	(600-1)	
	3 ⁷		D	1240-1¼	555	(600-1¼)	
			E	1240-1½	555	(600-1½)	
			CIR ⁸	ALL RWY	AB	1240-1	550
C					1240-1½	550	(600-1½)
D	1240-2	550			(600-2)		
		E	1520-3	830	(900-3)		

28 MAR 2019 to 25 APR 2019

28 MAR 2019 to 25 APR 2019

¹Opr 1300-0500Z++ Mon-Fri exc federal hol. OT upon req.

²When ALS inop, increase CAT ABCDE vis to ¾ mile.

³VGSI and PAR glide path not coincident.

⁴Visibility reduction by helicopters NA.

⁵When ALS inop, increase CAT ABC vis to 1 mile, CAT DE vis to 1¼ miles.

⁶When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1¼ miles, CAT E vis to 1½ miles.

⁷When ALS inop, increase CAT AB vis to 1 mile, CAT C vis to 1½ miles, CAT D vis to 1¾ miles, CAT E vis to 2 miles.

⁸Circling not authorized E of Rwy 21 and 33. Circling not authorized for CAT E to Rwy 8-26 and Rwy 15-33. Circling not authorized for CAT B, C, and D to Rwy 8.

RADAR INSTRUMENT APPROACH MINIMUMS