


APP CRS	Rwy Idg	<b>5810</b>
<b>336°</b>	TDZE	<b>1160</b>
	Apt Elev	<b>1175</b>

# RNAV (RNP) Z RWY 34

ROANOKE-BLACKSBURG RGNL/WOODRUM FIELD (R.O.A)

RNP AR APCH. RF required.	MALSRL	MISSED APPROACH: Climb to 6000 on track 336° to DMOSS, right turn to SETHB, right turn to JEEVY and on track 093° to PROSE and hold. * Missed approach requires minimum climb of 350 feet per NM to 4100. # Missed approach requires minimum climb of 415 feet per NM to 4100.
<p><b>▲</b> Missed approach requires RNP less than 1.0. For inop ALS, increase RNP 0.30* all Cats visibility to 1<math>\frac{1}{2}</math> SM. Inop table does not apply to RNP 0.30.</p> <p><b>✳</b>-13°C For uncompleted Baro-VNAV systems, procedure NA below -14°C or above 54°C.</p>		



ATIS <b>132.375</b>	ROANOKE APP CON <b>126.9 339.8</b>	ROANOKE TOWER <b>118.3 257.8</b>	GND CON <b>121.9 257.8</b>	CLNC DEL <b>119.7</b>
------------------------	---------------------------------------	-------------------------------------	-------------------------------	--------------------------



NE-3, 10 SEP 2020 to 08 OCT 2020

NE-3, 10 SEP 2020 to 08 OCT 2020

ELEV 1175	<b>D</b>	TDZE 1160
-----------	----------	-----------



CATEGORY	A	B	C	D
RNP 0.15 DA #		1495-1/2	335 (400-1/2)	
RNP 0.30 DA*		1646-1	486 (500-1)	
RNP 0.30 DA		2115-4	955 (1000-4)	

**AUTHORIZATION REQUIRED**