

RADAR MINS

20030

N1

RADAR INSTRUMENT APPROACH MINIMUMS

ATLANTIC CITY, NJ

Amdt 16, 04FEB16 (16035) (FAA)

ELEV 75

ATLANTIC CITY INTL (ACY)

RADAR-1 124.6 327.125 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	13		AB	480/24	405	(500-½)	CDE	480/40	405	(500-¾)
	4		AB	480-1	412	(500-1)	CDE	480-1½	412	(500-1½)
	31		AB	480/55	416	(500-1¼)	CDE	480/60	416	(500-1¼)
	22		AB	560-1	492	(500-1)	CDE	560-1¾	492	(500-1¾)
C CIRCLING	ALL RWY		A	560-1	465	(500-1)	B	600-1	525	(600-1)
			C	620-1½	545	(600-1½)	D	640-2	565	(600-2)
			E	760-2½	685	(700-2½)				

For inoperative MALSR, increase ASR S-13 CAT C/D/E visibility to RVR 6000.
Rwy 4 helicopter visibility reduction below ¾ SM not authorized.

MC GUIRE FLD, (JOINT BASE MC GUIRE DIX LAKEHURST) (KWRI),

NJ (Amdt 1, 18032 USAF)

ELEV 141

RADAR (E) - 119.05 120.0 269.025 **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	18*	3.0°/51/950	ABCDE	322-¾	200	(200-¾)
	36	3.0°/46/950	ABCDE	429-1	300	(300-1)

No-NOTAM MP: 0400-1100Z++ Mon-Fri, (by NOTAM if required).

PAR apch avbl 1200-0200Z++ Mon-Fri.

*Rwy 18, VGSI and PAR glidepaths not coincident.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20030

N1

NE-2

RADAR MINS


20030

N2

RADAR INSTRUMENT APPROACH MINIMUMS

WHEELER-SACK AAF (KGTB), NY (Fort Drum) (1-Amdt 1, 2-Orig-A 20030 USA)

ELEV **690**

RADAR¹- 124.875 257.6 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
RADAR-1 PAR	3 ² 3	3.0°/54/1038	ABCDE	885 -½	200	(200-½)
	21 ² 3	3.0°/58/1106	ABCDE	877 -½	200	(200-½)
	33 ⁴	3.0°/49/938	AB	938 -¾	250	(300-¾)
			CDE	938 -1	250	(300-1)
RADAR-2 ASR	21 ⁵		AB	1020 -½	343	(400-½)
			CDE	1020 -¾	343	(400-¾)
	15 ⁶		AB	1100 -½	413	(500-½)
			CD	1100 -¾	413	(500-¾)
			E	1100 -1	413	(500-1)
	33 ⁴		AB	1140 -1	450	(500-1)
			C	1140 -1¼	450	(500-1¼)
			DE	1140 -1½	450	(500-1½)
			E	1140 -1	450	(500-1)
	3 ⁷		AB	1240 -½	555	(600-½)
			C	1240 -1	555	(600-1)
			D	1240 -1¼	555	(600-1¼)
			E	1240 -1½	555	(600-1½)
CIR ⁸	ALL RWY	AB	1240 -1	550	(600-1)	
		C	1240 -1½	550	(600-1½)	
		D	1240 -2	550	(600-2)	
		E	1520 -3	830	(900-3)	

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

¹Opr 1500-0400Z++ Mon-Fri exc federal hol.

²When ALS inop, increase CAT ABCDE vis to ¾ mile.

³VGSI and PAR glide path not coincident.

⁴Visibility reduction by helicopters NA.

⁵When ALS inop, increase CAT ABC vis to 1 mile, CAT DE vis to 1¼ miles.

⁶When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1¼ miles, CAT E vis to 1½ miles.

⁷When ALS inop, increase CAT AB vis to 1 mile, CAT C vis to 1½ miles, CAT D vis to 1¾ miles, CAT E vis to 2 miles.

⁸Circling not authorized E of Rwy 21 and 33. Circling not authorized for CAT E to Rwy 8-26 and Rwy 15-33. Circling not authorized for CAT B, C, and D to Rwy 8.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20030

N2

NE-2