RNAV (GPS) Y RWY 13

ATLANTIC CITY INTL (ACY)

WAAS	APP CRS	Rwy ldg 10000
CH 45513	128°	TDZE 75
W13A		Apt Elev 75

For inoperative MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to 1½, and LNAV Cat D visibility to RVR 6000, Cat E visibility to 1½. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA.

ASR

MALSR

MISSED APPROACH: Climb to 2000 direct JURAD and on track 076° to RODDI and hold.

ATIS	ATLANTIC CITY APP CON	ATLANTIC CITY TOWER	GND CON	CLNC DEL
125.725 316.15	124.6 327.125	120.3 239.0	121.9 284.6	127.85 353.775





CATEGORY	A	B	C	D	E
LPV DA	275/18 200 (200-½)				
LNAV/VNAV DA	475/40 400 (400-¾)				475/50 400 (400-1)
LNAV MDA	520/24 445 (500-½)		520/40 445 (500-¾)	520/50 445 (500-1)	
CIRCLING	540-1 465 (500-1)		540-1½ 465 (500-1½)	640-2 565 (600-2)	760-2½ 685 (700-2½)



TDZ/CL Rwy 13
HIRL Rwys 4-22 and 13-31
REIL Rwy 31

NE-2, 05 NOV 2020 to 03 DEC 2020
NE-2, 05 NOV 2020 to 03 DEC 2020